### Reduce Specimen Identification Errors

#### while enhancing lean workflow

## Thermo Scientific SlideMate AS On-Demand Slide Printer

The Thermo Scientific™ SlideMate™ AS is the next generation Thermo Scientific Slide Printer delivering a smaller footprint than previous models, making it even easier to fit next to the microtome. The SlideMate AS promotes single piece workflow though unique features designed specifically for on-demand printing.

- Fully integrated color touch-screen and simple software are easy to use
- Built-in barcode scanner reads cassette information and imports the data to the slide label
- Connects easily to other computers or Laboratory Information Systems
- Prints directly onto the slide, eliminating the need for hand writing or labels

# Introducing the Thermo Scientific SlideMate AS On-Demand Slide Printer



SlideMate AS with optional slide delivery system



## "Slide labeling alone accounted for 67% of defects"

Source: The Henry Ford Production Systems Defects and Waste in Surgical Pathology as a Basis for Quality Improvement Initiatives

©2007 American Society for Clinical Pathology



# Printing using the SlideMate AS is as easy as 1, 2, 3...



1. Scan the cassette



2. Place the slide into the printer or use the slide delivery system



3. Pick up printed slide on the way to the waterbath

Description	Order Number
SlideMate AS Basic Printer SlideMate AS basic printer with color touchscreen, two USB ports, one ethernet port, bluetooth, power cord and simple software to print externally generated slide label from an image file	A83900001
SlideMate AS Basic Printing System SlideMate AS basic printer with slide delivery system, color touchscreen, two USB ports, one ethernet port, bluetooth, power cord and simple software to print externally generated slide label from an image file	A83900002
SlideMate AS On-Demand Printer SlideMate AS on-demand printer with color touch-screen, built-in scanner, two USB ports, one ethernet port, WI-FI, bluetooth, power cord and advanced software enabling label creation, special panel printing and import from LIS	A83900004
SlideMate AS On-Demand Printing System SlideMate AS on-demand printer with slide delivery system, color touch-screen, built-in scanner, two USB ports, one ethernet port, WI-FI, bluetooth, power cord and advanced software enabling label creation, special panel printing and import from LIS	A83900005
Thermal Transfer Ribbon	A83910001
Slide Delivery System	A83910002
Spare slide hopper for Slide Delivery System	A83920016
Gateway Software	A83910005
Printer Manager	A83910006

SlideMate AS Specifications	
Depth	9.1 in, 230 mm
Width	4.8 in, 122 mm
Height	11.5 in, 290 mm
Weight	9.5 lbs, 4 kg
Power requirements:	Universal 100 – 240 VAC, 50 – 60 Hz, 1.2A Max.
Slide type	1in x 3 in or 25 mm x 75 mm x 1mm
Print speed	5 seconds per slide
Media type	Thermal transfer ribbon
Media capacity	1 roll, approximately 12,000 slides per roll
Media color	Black
Connectivity	Ethernet, Wi-Fi, Bluetooth, USB (2)

#### www.thermoscientific.com/pathology

© 2015 Thermo Fisher Scientific Inc. All rights reserved. All other trademarks are the property of Thermo Fisher Scientific and its subsidiaries.

**Anatomical Pathology** 

Tudor Road, Manor Park Runcorn, WA7 1TA UNITED KINGDOM

4481 Campus Drive Kalamazoo, MI 49008 UNITED STATES +44 (0) 800 018 9396 +44 (0) 1928 534 000

+44 (0) 1320 334 000

+1 (800) 522-7270

